

VÁLVULAS BALBOA S. R. L.

Fábrica Reparación y Venta de válvulas Industriales, Bridas y Afines



RETENCIÓN SERIE 600 # (Altura del resalte: RF = 6.35 , RJ = 7.9)

Diámetro	NPS	1 1/2"	2"	2 1/2"	3"	4"	5"	6"	8"	10"	12"
	DN	40	50	65	80	100	125	150	200	250	300
Extremos	RF A	--	292.1	330.2	355.6	431.8	--	558.8	660.4	787.4	838.2
	RJ A1	--	295.3	333.4	358.8	435.0	--	562.0	663.6	790.6	841.4
	BW A2	--	292.1	330.2	355.6	431.8	--	558.8	660.4	787.4	838.2
Bridas	φ Exterior	--	165.1	190.5	210.0	273.0	--	355.6	419.1	508.0	558.8
	RJ N°	--	R23	R26	R30	R37	--	R45	R49	R53	R57
	Esp. S/Resalte	--	25.4	28.5	31.8	38.1	--	47.8	55.7	63.5	66.6
Circ. de Agujeros	--	127	149.4	168.2	215.9	--	292.1	349.3	431.8	489.0	
Cantidad	--	8	8	8	8	--	12	12	16	20	
Diam. de agujero	--	19	22	22	25	--	28	32	35	35	

RETENCIÓN SERIE 900 # (Altura del resalte: RF = 6.35 , RJ = 7.9)

Diámetro	NPS	1 1/2"	2"	2 1/2"	3"	4"	5"	6"	8"	10"	12"
	DN	40	50	65	80	100	125	150	200	250	300
Extremos	RF A	--	368.3	419.1	381.0	457.2	--	609.6	736.6	838.2	965.2
	RJ A1	--	371.5	422.3	384.2	460.4	--	612.8	739.8	841.4	841.4
	BW A2	--	368.3	419.1	381.0	457.7	--	609.6	736.6	838.2	965.2
Bridas	φ Exterior	--	215.9	244.3	241.3	292.1	--	381.0	469.9	546.1	609.6
	RJ N°	--	R24	R27	R31	R37	--	R45	R49	R53	R57
	Esp. S/Resalte	--	38.1	41.2	38.1	44.5	--	55.7	63.5	69.9	79.2
Circ. de Agujeros	--	165.1	190.5	190.5	235	--	317.5	393.7	469.9	533.4	
Cantidad	--	8	8	8	8	--	12	12	16	20	
Diam. de agujero	--	25.4	28.6	25.4	31.7	--	31.7	38.1	38.1	38.1	

RETENCIÓN SERIE 1500 # (Altura del resalte: RF = 6.35 , RJ = 7.9)

Diámetro	NPS	1 1/2"	2"	2 1/2"	3"	4"	5"	6"	8"	10"	12"
	DN	40	50	65	80	100	125	150	200	250	300
Extremos	RF A	--	368.3	419.1	469.9	546.1	--	704.9	831.9	--	--
	RJ A1	--	371.5	422.3	473.1	549.3	--	711.2	841.4	--	--
	BW A2	--	368.3	419.1	469.9	546.1	--	704.9	831.9	--	--
Bridas	φ Exterior	--	215.9	244.3	266.7	311.2	--	393.7	482.6	--	--
	RJ N°	--	R24	R27	R35	R39	--	R46	R50	--	--
	Esp. S/Resalte	--	38.1	41.1	47.8	53.8	--	82.6	91.9	--	--
Circ. de Agujeros	--	165.1	190.5	203.2	241.3	--	317.5	393.7	--	--	
Cantidad	--	8	8	8	8	--	12	12	--	--	
Diam. de agujero	--	25.4	28.4	31.8	35.1	--	38.1	44.5	--	--	